


TECHNICAL DATA SHEET



Type no.	P60 68	
Article no.	013560680101	
Standards	DIN EN 50342-1, 50342-2	
Application	Starter battery	
Electrical data		
Rated voltage	12V	
Rated capacity	60 Ah (K20)	
Cold start current	510 A (EN)	
Dimensions and weights		
Box	D23	
Length max.	233mm	
Width max.	173mm	
Box height max.	203mm	
Total height max.	225mm	
Battery weight	Ca. 15,5 kg (+/- 5 %)	
Electrolyte density	Approx. 1,28 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	60	
Pallet ID	Euro pallet	
Items per layer	20	
		
Features		
Base hold-down	B00	
Layout	0	
Terminal	1	
Separator	PE envelope separator	
Degassing	Battery with central degassing	
Flame arrester	Integrated	
Performance identification	W4 - C2 - V2 - E1	
Maintenance 1)		
Water consumption	W4	
Refill water	Distilled or demineralised (DIN 43530)	
Self-discharge	Approx. 3 % per month	
Charging current	Approx. 1/10 of the rated capacity	
Charging voltage 2)	max. 14,8 V	

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2018-04-01 ; Rights relating to changes and errors retained.
original